

## SECTION 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

Product Name: Ethyl acrylate 98%

Product Code: E04340

Supplier: Pfaltz & Bauer, Inc.  
172 E. Aurora Street  
Waterbury, CT 06708 USA

Phone: 203-574-0075

FAX: 203-574-3181

Emergency Phone: INFOTRAC, US: 1-800-535-5053  
INFOTRAC, INTERNATIONAL: +1-352-323-3500

## SECTION 2: HAZARDS IDENTIFICATION

Statement of Hazard: Environmentally hazardous, Flammable liquid, In use may form flammable/explosive vapour-air mixture, Irritant, Respiratory irritant, Skin sensitizer

Acute Health Hazard: Irritant to eyes, skin, mucous membranes and respiratory system. May be harmful by ingestion, skin absorption and inhalation.

Chronic Health Hazard: Target organ effect

HMIS Rating: H: 2 F: 3 P: 0

NFPA Rating: H: 2 F: 3 R: 0

To the best of our knowledge, the toxicological properties of this chemical have not been thoroughly investigated. Use appropriate procedures and precautions to prevent or minimize exposure.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

GHS Classification in accordance with Regulation (EC) No 1272/2008:

Acute toxicity, dermal (Category 4), H312  
Acute toxicity, inhalation (Category 4), H332  
Acute toxicity, oral (Category 4), H302  
Flammable liquids (Category 2), H225  
Hazardous to the aquatic environment, chronic toxicity (Category 2), H411  
Sensitization, skin (Category 1), H317  
Serious eye damage/eye irritation (Category 2A), H319  
Skin corrosion/irritation (Category 2), H315  
Specific target organ toxicity, single exposure (Category 2), H371  
Specific target organ toxicity, single exposure; Respiratory tract irritation (Category 3), H335

Pictogram:



Signal Word:

Danger

Hazard Statement(s):

H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H371 May cause damage to organs.  
H411 Toxic to aquatic life with long-lasting effects.

Precautionary Statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P240 Ground/bond container and receiving equipment.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.  
P302+P352 IF ON SKIN: wash with plenty of soap and water.  
P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

Supplemental Statement(s):

EUH018 In use may form flammable/explosive vapour-air mixture

**SECTION 3: COMPOSITION/INFORMATION on INGREDIENTS**

Chemical Name:

Ethyl acrylate 98%

Synonyms:

Acrylic acid ethyl ester; Ethyl 2-propenoate

CAS Number: 140-88-5  
MDL Number: MFCD00009188  
EINECS Number: 205-438-8  
Beilstein Registry Number: 773866  
Molecular Formula: C<sub>5</sub>H<sub>8</sub>O<sub>2</sub>  
Molecular Weight: 100.12  
Content: As specified in product name.

#### **SECTION 4: FIRST AID MEASURES**

Eye Contact: Flush eyes with large amounts of water for fifteen minutes. Separate eyelids with fingers. If irritation persists, seek medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

Inhalation: Move to a fresh air environment. Contact a physician if breathing becomes difficult.

#### **SECTION 5: FIRE FIGHTING MEASURES**

Flash Point (°C): -1

Explosion Limits: Lower, % by volume: 1.8  
Upper, % by volume: 12.1

Auto Ignition Temperature (°C): Not Available

Extinguishing Media: Carbon dioxide, dry chemical powder, alcohol-resistant foam, or water spray

Protective Equipment: Wear self-contained respirator and fully protective impervious suit.

Specific Hazards: May emit hazardous fumes under fire conditions. In use may form flammable/explosive mixture.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal Protection: Wear a self-contained breathing apparatus, rubber boots and gloves, and disposable coveralls. Dispose of coveralls after use. Remove from ignition sources if safe to do so. Follow emergency response plan and contact proper authorities if needed.  
Keep unprotected persons away.

Environmental Protection: Keep spills out of sewers and bodies of water. Dike and contain the spill with inert material. Absorb on sand, vermiculite or diatomite. Transfer material to a container for disposal or recovery. Ventilate area and wash spill site after material pickup is complete.

## **SECTION 7: HANDLING and STORAGE**

Handling and Storage: Avoid breathing dust, vapor, mist or gas. Avoid contact with skin and eyes. Avoid prolonged or repeated exposure. Use only in a chemical fume hood. Open and handle container with care. Keep ignition sources away.  
Store in a tightly closed container in a dry, well-ventilated place.

Sensitivities: Air, Light

Storage Temperature (°C): 2 to 8

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls: Use product in a well ventilated area or under a fume hood. Use proper lab equipment while handling this product. Keep away from incompatible materials for possible risk of hazardous reaction.

Eye Protection: Wear appropriate protective eyeglass or chemical safety goggles. Make sure that there is an eyewash station in your vicinity.

Skin Protection: Wear impervious gloves and protective clothing.

Respiratory Protection: Use a NIOSH approved respirator when exposure limits are exceeded or if irritation or other symptoms are experienced.

<u>Exposure Limits:</u>	<u>Country</u>	<u>Source</u>	<u>Type</u>	<u>Value</u>
	USA	ACGIH	TWA	5 ppm
	USA	OSHA	STEL	25 ppm
	USA	OSHA	PEL	Not Available

## **SECTION 9: PHYSICAL and CHEMICAL PROPERTIES**

Appearance: Clear colorless liquid

Odor: Acrid

Odor Threshold: Not Available

<u>Flash Point (°C):</u>	-1
<u>Auto Ignition Temperature (°C):</u>	Not Available
<u>UEL % by Volume:</u>	12.1
<u>LEL % by Volume:</u>	1.8
<u>Melting Point (°C):</u>	-71
<u>Boiling Point (°C):</u>	99-100
<u>Evaporation Rate:</u>	Not Available
<u>pH Value:</u>	Not Available
<u>Density (g/cm<sup>3</sup>):</u>	0.924
<u>Refractive Index (n<sup>20</sup><sub>D</sub>):</u>	1.4060
<u>Viscosity:</u>	Not Available
<u>Solubility in Water:</u>	Slightly soluble, 1.5 g/L
<u>Solubility in Other:</u>	Slightly soluble in EtOH, DMSO, Chloroform, Alcohol, Ethyl ether
<u>Vapor Pressure (mmHg):</u>	31
<u>Vapor Density (Air=1):</u>	3.5

## **SECTION 10: STABILITY and REACTIVITY**

<u>Stability:</u>	Stable under normal temperatures and pressures.
<u>Incompatibility:</u>	Oxidizing agents, Peroxides
<u>Reactivity:</u>	Product may react with incompatible materials to release other hazardous substances.
<u>Conditions to Avoid:</u>	Heat, flame, sparks, other ignition sources.
<u>Hazardous Decomposition Products:</u>	Carbon oxides

## **SECTION 11: TOXICOLOGICAL INFORMATION**

RTECS Reference: AT0700000

Target Organs: Liver, Kidney

Toxicity Data:

Oral Rat LD <sub>50</sub> mg/kg:	800.00
Dermal Rabbit LD <sub>50</sub> mg/kg:	2997.00
Intraperitoneal Rat LD <sub>50</sub> mg/kg:	450.00
Inhalation Rat LC <sub>50</sub> , mg/m <sup>3</sup> - h:	1414.00 - 4

Carcinogenicity: National Toxicology Program (NTP) listed:  
Not Available

International Agency for Research on Cancer (IARC) listed: Not Available

Potential Symptoms: Not Available

## **SECTION 12: ECOLOGICAL INFORMATION**

Toxicity: Flathead minnow LC<sub>50</sub>: 2.50 mg/l - 2.50 hrs.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Contact a licensed professional waste disposal service. Dispose in a manner consistent with federal, state and local environmental regulations.

## **SECTION 14: TRANSPORT INFORMATION**

DOT Shipping Name: Ethyl Acrylate, Stabilized

DOT UN Number: UN1917

DOT Hazard Class: Class 3

DOT Packing Group: PGII

Reportable Quantity: 1000 lbs

IMDG Shipping Name: Ethyl Acrylate, Stabilized

IMDG UN Number: UN1917

IMDG Hazard Class: Class 3

IMDG Packing Group: PGII

Marine Pollutant: No  
IATA Shipping Name: Ethyl Acrylate, Stabilized  
IATA UN Number: UN1917  
IATA Hazard Class: Class 3  
IATA Packing Group: PGII

## **SECTION 15: REGULATORY INFORMATION**

### United States

Toxic Substance Control Act (TSCA) listed: Yes  
Superfund Amendments and Reauthorization Act (SARA 302) listed: No  
Superfund Amendments and Reauthorization Act (SARA 311/312) listed: No  
Superfund Amendments and Reauthorization Act (SARA 313) listed: Yes

### European Union

European Inventory of Existing Chemical Substances (EINECS): 205-438-8  
GHS Classification in accordance with Regulation (EC) No 1272/2008: Yes

### Canada

Canadian Domestic Substances List (DSL) listed: Yes  
Canadian Non-Domestic Substances List (NDSL) listed: No

## **SECTION 16: OTHER INFORMATION**

Date Prepared: 9/26/2022

The information above is presented in good faith. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty with respect to such information and we assume no liability resulting from its use. The user should consider this information as a supplement to other information that may be available and make independent judgement to ensure proper use to protect the health and safety of employees and the environment. Pfaltz and Bauer shall not be held liable for any damage resulting from handling or from contact with the above product.