

SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

<u>Product Name:</u> Isopropyl alcohol 99%

Product Code: I08810

Supplier: Pfaltz & Bauer, Inc.

172 E. Aurora Street

Waterbury, CT 06708 USA

Phone: 203-574-0075

FAX: 203-574-3181

Emergency Phone: INFOTRAC, US: 1-800-535-5053

INFOTRAC, INTERNATIONAL: +1-352-323-3500

SECTION 2: HAZARDS IDENTIFICATION

<u>Statement of Hazard:</u> Flammable liquid, In use may form flammable/explosive vapour-air

mixture, Irritant, Narcotic effects, Respiratory irritant

Acute Health Hazard: Irritant to eyes, skin, mucous membranes and respiratory system.

May be harmful by ingestion, skin absorption and inhalation.

Chronic Health Hazard: Not Available

HMIS Rating: H: 2 F: 3 P: 0

NFPA Rating: H: 2 F: 3 R: 0

To the best of our knowledge, the toxicological properties of this chemical have not been thoroughly investigated. Use appropriate procedures and precautions to prevent or minimize exposure.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS): GHS Classification in accordance with Regulation (EC) No 1272/2008:

Acute toxicity, dermal (Category 4), H312 Acute toxicity, inhalation (Category 4), H332

Acute toxicity, oral (Category 4), H302

Flammable liquids (Category 2), H225

Serious eye damage/eye irritation (Category 2A), H319

Skin corrosion/irritation (Category 2), H315

Specific target organ toxicity, single exposure; Narcotic effects (Category 3), H336

Specific target organ toxicity, single exposure; Respiratory tract irritation (Category 3), H335

Pictogram:





Signal Word: Danger

<u>Hazard Statement(s):</u> H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

<u>Precautionary Statement(s):</u> P210 Keep away from heat/sparks/open flames/hot surfaces. — No

smoking.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/[

1/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician

IF you feel unwell.

P302+P352 IF ON SKIN: wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in

a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P332+P313 IF SKIN irritation occurs: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental Statement(s): EUH018 In use may form flammable/explosive vapour-air mixture

SECTION 3: COMPOSITION/INFORMATION on INGREDIENTS

Chemical Name: Isopropyl alcohol 99%

<u>Synonyms:</u> 2-Propanol; IPA; Isopropanol; Dimethylcarbinol

<u>CAS Number:</u> 67-63-0

MDL Number: MFCD00011674

EINECS Number: 200-661-7

Beilstein Registry Number: 635639

Molecular Formula: C₃H8O

Molecular Weight: 60.10

Content: As specified in product name.

SECTION 4: FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water for fifteen minutes. Separate

eyelids with fingers. If irritation persists, seek medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, seek medical

attention.

<u>Ingestion:</u> Do not induce vomiting. Seek medical attention.

Inhalation: Move to a fresh air environment. Contact a physician if breathing

becomes difficult.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point (°C):

Explosion Limits: Lower, % by volume: Not Available

Upper, % by volume: 12.7

<u>Auto Ignition</u>

Temperature (°C):

Not Available

<u>Extinguishing Media:</u> Carbon dioxide, dry chemical powder, alcohol-resistant foam, or water

spray

<u>Protective Equipment:</u> Wear self-contained respirator and fully protective impervious suit.

<u>Specific Hazards:</u> May emit hazardous fumes under fire conditions. In use may form

flammable/explosive mixure.

SECTION 6: ACCIDENTAL RELEASE MEASURES

<u>Personal Protection:</u> Wear a self-contained breathing apparatus, rubber boots and gloves,

and disposable coveralls. Dispose of coveralls after use. Remove from ignition sources if safe to do so. Follow emergency response plan and

contact proper authorities if needed. Keep unprotected persons away. Environmental Protection: Keep

Keep spills out of sewers and bodies of water. Dike and contain the spill with inert material. Absorb on sand, vermiculite or diatomite. Transfer material to a container for disposal or recovery. Ventilate area and wash spill site after material pickup is complete.

SECTION 7: HANDLING and STORAGE

Handling and Storage: Avoid breathing dust, vapor, mist or gas. Avoid contact with skin and

eyes. Avoid prolonged or repeated exposure. Use only in a chemical fume hood. Open and handle container with care. Keep ignition sources

away.

Store in a tightly closed container in a dry, well-ventilated place. Store

under inert gas. Store under nitrogen.

Sensitivities: Not Available

Storage Temperature (°C): 15 to 30

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Engineering Controls:</u> Use product in a well ventilated area or under a fume hood. Use proper

lab equipment while handling this product. Keep away from incompatible materials for possible risk of hazardous reaction.

Eye Protection: Wear appropriate protective eyeglass or chemical safety goggles. Make

sure that there is an eyewash station in your vicinity.

Skin Protection: Wear impervious gloves and protective clothing.

Respiratory Protection: Use a NIOSH approved respirator when exposure limits are exceeded or

if irritation or other symptoms are experienced.

Exposure Limits: <u>Country</u> <u>Source</u> <u>Type</u> <u>Value</u>

USA ACGIH TWA 200 ppm
USA OSHA STEL 500 ppm

USA OSHA PEL Not Available

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Appearance: Colorless liquid

Odor: Alcohol-like

Odor Threshold: Not Available

Flash Point (°C):

<u>Auto Ignition</u>

Temperature (°C):

Not Available

UEL % by Volume:

12.7

LEL % by Volume:

Not Available

Melting Point (°C):

-90-(-85)

Boiling Point (°C):

82

Evaporation Rate:

Not Available

pH Value:

Not Available

Density (q/cm³):

0.785

Refractive Index (n²⁰_D):

1.3770

Viscosity:

Not Available

Solubility in Water:

Soluble

Solubility in Other:

Soluble in Alcohol, Ether, Chloroform

Vapor Pressure (mmHg):

Not Available

Vapor Density (Air=1):

Not Available

SECTION 10: STABILITY and REACTIVITY

Stability:

Stable under normal temperatures and pressures.

Incompatibility:

Oxidizing agents, acid anhydrides, aluminium, Halogenated compounds,

acids

Reactivity:

Product may react with incompatible materials to release other

hazardous substances.

Conditions to Avoid:

Heat, flame, sparks, other ignition sources.

<u>Hazardous</u>

Carbon oxides

Decomposition Products:

SECTION 11: TOXICOLOGICAL INFORMATION

RTECS Reference:

NT8050000

Target Organs: Nerves, Kidney, Cardiovascular system, Gastrointestinal tract, Liver

Toxicity Data: Oral Rat LD₅₀ mg/kg: 5045.00

Dermal Rabbit LD₅₀ mg/kg: 12800.00 Inhalation Rat LC₅₀, mg/m3 - h: 16000.00 - 8

<u>Carcinogenicity:</u> National Toxicology Program (NTP) listed:

Not Available

International Agency for Research on Cancer (IARC) listed: Not

Available

<u>Potential Symptoms:</u> Not Available

SECTION 12: ECOLOGICAL INFORMATION

<u>Toxicity:</u> Flathead minnow LC₅₀: 9640.00 mg/l - 9640.00

Water flea LC₅₀: 5102.00 mg/l - 5102.00 Green Algae LC₅₀: 2000.00 mg/l - 72 hrs.

SECTION 13: DISPOSAL CONSIDERATIONS

Contact a licensed professional waste disposal service. Dispose in a manner consistent with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Isopropyl Alcohol

DOT UN Number: UN1219

DOT Hazard Class: Class 3

DOT Packing Group: PGII

IMDG Shipping Name: Isopropyl Alcohol

IMDG UN Number: UN1219

IMDG Hazard Class: Class 3

IMDG Packing Group: PG II

Marine Pollutant: No

IATA Shipping Name: Isopropyl Alcohol

IATA UN Number: UN1219

IATA Hazard Class: Class 3

IATA Packing Group: PG II

SECTION 15: REGULATORY INFORMATION

United States

Toxic Substance Control Act (TSCA) listed: Yes

Superfund Amendments and Reauthorization Act (SARA 302) listed: No

Superfund Amendments and Reauthorization Act (SARA 311/312) listed: No

Superfund Amendments and Reauthorization Act (SARA 313) listed: Yes

European Union

European Inventory of Existing Chemical Substances (EINECS): 200-661-7

GHS Classification in accordance with Regulation (EC) No 1272/2008: Yes

Canada

Canadian Domestic Substances List (DSL) listed: Yes

Canadian Non-Domestic Substances List (NDSL) listed: No

SECTION 16: OTHER INFORMATION

Date Prepared: 6/21/2023

The information above is presented in good faith. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty with respect to such information and we assume no liability resulting from its use. The user should consider this information as a supplement to other information that may be available and make independent judgement to ensure proper use to protect the health and safety of employees and the environment. Pfaltz and Bauer shall not be held liable for any damage resulting from handling or from contact with the above product.